


AIW-162BS

IEEE 802.11ax/ac/a/b/g/n + Bluetooth 5.0
M.2 2230 E key Card



IC CE FCC

Features

- Perfectly fit for Rockchip platform
- Bluetooth 5.0
- 2Tx/ 2Rx
- 64/128 bit WEP, WPA, WPA2, WPA3, 802.1x
- Operating temperature: -40 to 85 °C

Specifications

| | |
|------------------------|---|
| Main Chipset | Broadcom BCM43752 |
| Tx/Rx | 2Tx/ 2Rx (2 IPEX MHF1 connector Receptacle) |
| Standard Conformance | Wi-Fi 6 + BT5.0 |
| Form Factor | M.2 E key |
| Interface | Wi-Fi: PCIe, Bluetooth: UART |
| Operation Voltage | DC 3.0 ~ 3.3V |
| Power Consumption | TX Mode: 660mA (Max) |
| Security | 64/128 bit WEP, WPA, WPA2, WPA3, 802.1x |
| O.S Supported | Linux/Android |
| Temperature Ranges | Operation: -40 to 85 °C |
| Dimensions (L x W x H) | 30 x 22 x 2.8 mm |

Ordering Information

| Part No. | Product Description |
|---------------|---|
| AIW-162BS-G11 | Advantech Brand, Wi-Fi 6 + BT 5.0, BCM43752, 2T2R, M.2 2230 E key |

Suggested Antenna and Cable

| Model | Part No. | Specifications |
|---------|---------------|---|
| AIW-512 | 1751000651-01 | Omni-directional radiation pattern, compatible for WiFi5/6/6E/7 |
| AIW-513 | 1751000717-01 | Omni-directional radiation pattern, compatible for WiFi5/6/6E/7, IP67 level |
| | 1751000648-01 | WiFi Coaxial Cable, 10cm, RP-SMA female to IPEX4 |
| | 1751000622-01 | WiFi Coaxial Cable, 15cm, RP-SMA female to IPEX4 |
| | 1751000635-01 | WiFi Coaxial Cable, 20cm, RP-SMA female to IPEX4 |
| | 1751000621-01 | WiFi Coaxial Cable, 25cm, RP-SMA female to IPEX4 |
| | 1751000620-01 | WiFi Coaxial Cable, 30cm, RP-SMA female to IPEX4 |