# **EWM-W180H01E**IEEE 802.11ac/a/b/g/n + Bluetooth 5.0 Half-Size MiniPCle Card



#### **Features**

- USB interface in minPCle form factor
- Bluetooth 5.0
- 64/128 bit WEP, WPA, WPA2, WPA3, 802.1x
- Operating temperature: -20 to 70 °C

### **⊜ IC C€ FCC**

#### **Specifications**

Main Chipset	Realtek RTL8822CU		
Tx/Rx	2Tx/ 2Rx (2 IPEX MHF1 connector Receptacle)		
Standard Conformance	Wi-Fi 5 + BT5.0		
Form Factor	MiniPCle		
Interface	vace Wi-Fi: USB, Bluetooth: USB		
Operation Voltage	DC 3.0 ~ 3.3V		
Power Consumption	Consumption TX Mode: 600mA (Max)		
Security	urity 64/128 bit WEP, WPA, WPA2, WPA3, 802.1x		
O.S Supported	orted Windows/Linux/Android		
Temperature Ranges	erature Ranges Operation: -20 to 70 °C		
Dimensions (L x W x H)	29.9 x 26.6 x 3 mm		

#### **Ordering Information**

Part No.	Product Description	
EWM-W180H01E	Advantech Brand, Wi-Fi 5 + BT 5.0, RTL8822CU, 2T2R, Half-size MiniPCle	

## **Suggested Antenna and Cable**

	Model	Part No.	Specifications
	AIW-512	1751000651-01	Omni-directional radiation pattern, compatible for WiFi5/6/6E/7
	AIW-513	1751000717-01	Omni-directional radiation pattern, compatible for WiFi5/6/6E/7, IP67 level
		1751000647-01	WiFi Coaxial Cable, 10cm, RP-SMA female to IPEX1
		1751000627-01	WiFi Coaxial Cable, 15cm, RP-SMA female to IPEX1
		1751000634-01	WiFi Coaxial Cable, 20cm, RP-SMA female to IPEX1
		1751000626-01	WiFi Coaxial Cable, 25cm, RP-SMA female to IPEX1
		1751000588-01	WiFi Coaxial Cable, 30cm, RP-SMA female