



Fanless Panel PC

10,1" Embedded CPU

OVPPC-101-I512-FHD

The overall use of flat aluminum alloy panel, fanless fully enclosed integrated design. Meet the requirements of different equipment in different environments. It is widely used in industrial control, military, communication, power, network, intelligent self-service terminal equipment and other automation applications.

## Features

- 3mm Super Thin Front Bezel, Best for Embedded Cabinet.
- Pure flat panel IP65 dust-proof and waterproof.
- High precision aluminum alloy material.
- Self-developed fanless X86 architecture industrial motherboard
- Dual gigabit adaptive Ethernet ports for faster transmission.
- Industrial protection, applicable to various harsh environments.
- Supporting 12V-36V wide voltage power supply;
- Rich interfaces and strong extensibili.



## Product Model

Product Size	10.1"
Non-touch	OVPPC-101G-I512-FHD
Capacitive touch	OVPPC-101C-I512-FHD
Resistive touch	OVPPC-101R-I512-FHD

## Product Interface



## Product Specifications

### Screen Parameters

LCD Size	10.1" TFT LCD
Resolution	1920x1080
Viewing Angle	85/85/85/85 (L/R/U/D)
Colour	16.7M
Brightness	300 cd/m <sup>2</sup>
Contrast ratio	1000:1

### Touch Screen

Touch screen type	10 point touch projection capacitive touch screen
Light transmittance	≥88%
Input mode	Handwriting or capacitive pen
Controller communication	USB


### Hardware Configuration

CPU	I5-1235U
CPU frequency	4.4GHz
Integrated graphics	Intel UHD620 Graphics
RAM	8G DDR4(Optional 16G/32G /64G)
Storage	128G SSD (Optional 256/512G)
WiFi	2.4GHz / 5GHz dual bands
Bluetooth	BT4.0(Optional)
Operating system	Windows7/10/11; Ubuntu16.04.7/8.04.5/20.04.3/24.04; Centos7.6/7.8
Other support	Support RTC real-time clock and timing switch

### Power parameters

Input voltage	DC 12V~36V	Static power	18W
---------------	------------	--------------	-----

## Product size



### Physical Characteristics (Get confirmation before placing your order.)

Overall dimensions	W293.6x H193.6x D58mm
Size of opening	W276.5x H176.5mm

### Interface

DC	1*DC 2.5
HDMI	1*HDMI, Support HDMI data output, maximum support 1080P
USB	2*USB 2.0 2*USB 3.0
LAN	2*LAN,Dual 1000M adaptive Ethernet
AUDIO	1*Audio I/O,Support audio input and output
SMI card	Standard SIM card interface, supporting various standards (depending on 3G/4G module)
VGA	1*VGA
RS232	2*RS232(Optional RS485,RS422,GPIO)
POWER	1*POWER
Industrial terminal	1*Industrial terminal

### Product Reliability

Working Temperature	-20°C to 60°C
Storage temperature	- 40°C to 70°C
Relative humidity	Humidity: 95% Non-Condensing
Vibration protection	IEC 60068-2-64, random, 5 ~ 500 Hz, 1 hr/axis
Impact protection	IEC 60068-2-27, half sine wave, duration 11ms
Authentication	CCC/CE/FCC/EMC/CB/ROHS
Waterproof	Front panel reaches IP65 protection level